



# KE-24TBA



## 24-Port 10Base-T/2/5 Ethernet Hub

### Key Features:

- Complies with IEEE 802.3 10Base-T, 10Base2, 10Base5 standards
- 24-Port 10Mbps Ethernet Hub
- Plug-and-Play installation
- Automatic partitioning of faulty ports
- MDI-II Uplink port for easy expansion
- Easy-to-View diagnostic LED provide status for each port
- 19" rackmountable

### Specifications:

Number of ports	22TP, 1BNC, and 1AUI ports	
Protocol	CSMA/CD	
Topology	Star	
Transfer Rate	10Mbps	
Connectors	TP port BNC port AUI port	Shielded RJ-45 BNC female connector AUI DB-15 male connector
Cables	UTP Cat. 3, 4, 5 (100m max.) BNC RG-58A/U 50-ohm coaxial cable (185m max.) AUI drop cable (50m max.)	
LEDs	- Power, Collision status, - Reception status forAUI and BNC port, - Link/Rx for each TP port	
Environment	Operating Temperature: Relative Humidity:	0° to 40° C 10% ~ 90% non-condensing
Dimension	440mm x 44mm x 122mm	(17.32 x 1.73 x 4.8inch)
Power	100 - 250 VAC, 50/60Hz, 19W	



FCC Part 15, Class A  
CISPR 22 Class A

### **KTI Networks Inc.**

7400 Harwin Dr., Suite 120  
Houston, Texas 77036 U.S.A.  
Tel: 713-266-3891  
Fax: 713-266-3893  
E-mail: [kti@ktinet.com](mailto:kti@ktinet.com)  
URL: <http://www.ktinet.com>

### **Katron Technologies Inc.**

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,  
Hsi-chih, Taipei Hsien, Taiwan, R.O.C.  
Tel: 886-2-2698-3878  
Fax: 886-2-2698-3873  
E-mail: [kti@ktinet.com](mailto:kti@ktinet.com)  
URL: <http://www.ktinet.com.tw>

Trademarks: All brand names are trademarks or registered trademarks of their respective holders. This information is subject to change without prior notice.